The Little Ann Assembly Instruction By Laser Dollhouse Designs



Parts for assembly



Door Assembly



Roof Assembly





1st Floor Walls 1A , 1E, & 1F



Porch rails 1A, 1B & 1C



Subfloor Assembly S1 thru S4



Plexiglas



2nd Floor Assembly 2A, 2B & Fretwork



 $\mathbf{1}^{st}$ and $\mathbf{2}^{nd}$ Floors



Fence Assembly



Window Frames



Base Floor

Step 1. locate the Base floor and position as seen in Figure 1







Step 2. Locate Subfloor Assembly S1 thru S4 and insert S1 thru S4 tabs into Base floor matching Slots S1-S4 as seen in Figure 2



Step 3. Take the First floor marked 1A thru 1F and insert on top of assembled subfloor by aligning open slots to tabs. Refer to figure 3.

Step 4. Take 1A Wall and insert into slot 1A on first floor. Then insert door assembly thru cutout for the door opening. Refer to figure 4 and 5.











Figure 3

Step 5. Take the two rectangle and one half circle Plexiglas cutouts and insert into openings from the interior side of wall. Finally secure by placing the interior door frame in place. Refer to figure 6, 7 and 8.



Figure 6



Figure 7



Step 6. Take the porch rail 1A, 1B and 1C and insert into slots 1A-1C. Also place walls 1E and 1F into respective slots on first floor. Refer to figure 9.



Step 7. Place window frame on exterior of walls 1E and 1F Refer to figure 10.



Figure 10

Step 8. Place window Plexiglas cutouts into cutouts of walls 1E and 1F from the interior side and then place interior frames to secure. See figures 11 and 12.





Figure12

Figure11

Step 9. Secure first floor by inserting second floor on top and aligning cutout tabs to slots on top of first floor rails and walls. See figures 13



Figure13

Step 10. Place second floor walls 2A and 2b into slots provided. Refer to figure 14



Figure14

Step 11. Place window frame and Plexiglas into 2A as done with walls 1E and 1F. See figure 15



Step 12. Align and place one side of the roof making sure the cut slots closest to the top are up as in figure 16



Figure16

Note: Two front cutout,

The most forward cutouts closest to the top is right side up

facing.

Step 13. Place fretwork into roof by matching tabs and slots. See figure 17



Step 14. Now add the other side of the roof by matching the tabs and slots. Refer to figure 18



Figure18

Step 15. Locate the post as seen in figure 19. This post fits to the front right forward corner. Place fence rail as seen in figure 20 into the side of post and into base. Once in place should be as in figure 21





Figure20



Figure21

Step 16. Locate the fence rail as seen in figure 22 and add to opening in post. Next locate post as seen in figure 23 and insert fence and post to base. The circle to hold functioning gate should be at bottom.





Figure23

Figure22 Step 17. Locate final fence rail with swing gate along with remaining side fence and insert into

base as seen in figure 24



Step 18. Take stairs assembly and place within fence as seen in figure 25



Figure25



The Little Ann is now completed. Time for some Happy decorating!!!

Laser Dollhouse Designs <u>www.laserdollhouses.com</u> Email: laserdollhouses@aol.com